

Premier Hygienic Ceiling Systems

Suitable Substrates

Please consult Be-plas regarding suitable ceiling substrates.

Installation Temperature

A minimum ambient temperature of 14°C/57°F is required.

Panels

Supplier: Beplas Hygienic Walls and Ceilings Ltd, Helix Business Park, New Bridge Road, Ellesmere Port, Wirral CH65 4LR

PVC Twin Wall Tongue & Groove Panel

Reference:	Description:	Size:
50.1.85703	Premier PVC T&G	3000 x 250 x 10mm Colour White
50.1.85704	Premier PVC T&G	4000 x 250 x 10mm Colour White
50.1.8570	Premier PVC T&G	5000 x 250 x 10mm Colour White
50.1.85706	Premier PVC T&G	6000 x 250 x 10mm Colour White

Fire Rating

Certified to BS476 Part 7 Class 1. Certified to BS476 Part 6 Class 0 when attached to a non-combustible substrate.

Method of Fixing

Mechanically fix to existing ceiling substrate or PVC battens (Ref. B810L) at max. 600mm centres. Or use Beplas adhesive (GPPA or PP310). Ask for Premier PVC Fixing Instructions.

Edge Detail

Abutments to walls, use PVC perimeter trims (Ref. 50.1.8240). Intermediate Joint Detail Use PVC division bars (Ref. 50.1.8242).

Finishing

Apply Be-plas FDA approved silicone sealant (Ref. PSNW) in mouldings and around all accessories and/or fixtures.

Accessories

Surface mounted accessories should be attached to ceiling substrate. PVC battens for mounting (Ref. B810L)