

Elite Multiplank

Hygienic Wall Partitioning Systems

Installation Temperature

A minimum temperature of 10°C/50°F is required.

Panels

Supplier: Beplas Hygienic Walls and Ceilings Ltd, Helix Business Park, New Bridge Road, Ellesmere Port, Wirral CH65 4LR

Reference:	Description:	Size:
BP300L/W3	Multiplank 3m	3000 x 300 x 35mm Colour White
BP300/LW	Multiplank 4m	4000 x 300 x 35mm Colour White

Other sizes available to order.

Fire Rating

All products certified to BS476 Part 7 Class 1.

Method of Fixing

Fix channel to floor and manoeuvre panels into position, clicking each panel together where they meet on the vertical.

Joint Detail

Click system at vertical joints. For horizontal joints:

Reference:	Size:
DB3530	3000mm

Edge Detail

Exposed panel edges should be closed with high impact PVC channel sections:

Reference:	Size:
CS353.0	3000mm

Corner Detail

Internal corners and external should be connected with high impact PVC corner section:

Reference:	Size:
MPC35	3000mm

Finishing

Apply Beplas food grade silicone sealant (Ref. PSNW) in mouldings and around all panel edges and fixtures.

Service Preparations

Allow a 3-4mm gap around all holes and panels.